

P-xx-100 - Insulation Hangers

Description	Self-adhesive metal insulation hangers for fixing of pre-formed insulation material to metal ducting only. P-45-100, 45mm pins P-62-100, 62mm pins
Product properties	Spindles: Aluminium. Bases: 0,4mm galvanized steel. Washers: Ø30mmgalvanized steel. Foam: Polyethylene foam with acrylic adhesive and a liner.
Storage and ageing	1 year shelf life whilst stored in original packaging and 5-25°C room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be dry, clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure. Do not touch the adhesive with fingers. Position carefully the slap over the pins, then press uniformly until the insulation butts firmly against the base. Fit self-locker washers (dome side outwards) to hte pins and press up to the insulation surface. Do not compress the insulation. Excess pin lengths are then snipped off, and should not be bent over insulation. When snipping off excess pin length, hold pliers steady and do not work from side to side.

TECHNICAL DATA

Carrier	PE/foam	
Adhesive	Acrylic	
Service temperature	Between -20 and 80 °C	Between -4 and 176 °F
Application temperature	Minimum 5 °C	Minimum 41 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Denmark A/S
 Gydevang 40
 3450 Allerød
 tel +45 - 48 17 12 11
 fax +45 - 48 17 40 52
 www.stokvistapes.dk
 info@stokvistapes.dk